



DATI TECNICI															
	Continui		Emergenza		Motore	Avviamento	N° Cilindri	Potenza	Cilindrata	Consumo					
Modello	[KVA]	[KW]	[KVA]	[KW]				Hp/kW	Lt	lt/hr	lt	Kg	mm	Kg	mm
CGM 3H	3	2,7	3,3	2,9	GX160	S	1	4,8/3,6	163	1	3,6	37	580x410x410h	/	/
CGM 3,6H	3,6	3,2	4,2	3,8	GX200	S	1	5,5/4,1	196	1,1	3,6	38	580x410x410h	/	/
CGM 5,5H	5,5	4,4	6	4,8	GX270	S / E	1	8/6	270	1,6	6	58/76	740x450x500h	140	1100x550x600h
CGM 7H	7	5,6	7,7	6,1	GX390	S / E	1	11/8,2	389	2	6,5	75/82	740x450x500h	150	1100x550x600h
CGM 10B	10	8	11	8,8	16HP	S / E	2	16/11,8	480	3,8	8,5	97/115	860x550x650h	/	/
CGM 12B	12	9,6	13,2	10,5	18HP	S / E	2	18/13,2	570	4,3	8,5	111/125	860x550x650h	/	/

* S= Strappo E= Elettrico